


INTRODUCING THE NEW

Attendant 4U™

Fuel and Fluid Management System



The NEW **Attendant 4U™** provides you with the best value in small to medium sized fuel and fluid management systems.

Controlling up to 4 hoses, **The Attendant 4U™** gives you the security, accountability and simplicity you have come to expect from **asi**.

You can validate both drivers and vehicles, collect hours or odometers, and have all the information you need on your PC using the companion software, **WinFuel 4U™**. Connect your **Attendant 4U™** to your PC by a wired connection, wireless radio, Ethernet, dial-up or through the cellular network.

With the optional Touch Memory™ or proximity card access, you gain even more security, at a price that makes **The Attendant 4U™** a great value.

The Attendant 4U™ has over 20 reports and lists that are easy to read and excellently organized. They help you sort through your data and find the right information, quickly, that you need to run your operation. Reports like Transactions by Date, Sequence Number, Vehicle, Divisions and Operators are just a few of them.

Inventory control is a snap with continual inventory and totalizer readings from **The Attendant 4U™**. And with the ability to enter fuel deliveries, dips and tank gauge readings into **WinFuel 4U™**, inventory reconciliation is a breeze.



FEATURES AND BENEFITS

- MULTI-SITE CAPABILITY; up to 4 sites
- Communicate to your PC by direct cable, wireless, ethernet
- over 25 standard lists and reports
- controls 2 or 4 hoses
- track up to 40 divisions, 400 vehicles & 400 operators
- Inventory and totalizer readings with every communication
- Automated tasks include polling, exports
- Export to Excel or ASI Lifetime Standard Export

CALL TODAY FOR A QUOTE

alternate solutions inc.

565 Arvin Ave. Stoney Creek, ON L8E 5N7
Phone: 905-643-8289 / Fax: 905-643-2619
www.asifluid.com

INTRODUCING THE NEW

Attendant 4U™

Fuel and Fluid Management System



ISLAND ENTRY UNIT

- weatherproof stainless steel keypad
- backlit display for easy access at night
- attractive, long lasting stainless steel pedestal
- preset maximum fuel limits and tank capacities
- no heater required

SECURITY

- Standard access by keypad entry of Operator and Vehicle numbers
- Optional Touch Memory™ keys for Operators with P.I.N.
- Proximity cards for Operators with P.I.N.
- Odometer or Hour reasonability check
- Detailed reports and messages for all activity at the pumps

TECHNICAL SPECIFICATIONS

THE ATTENDANT 4U™ ISLAND UNIT

ATTENDANT 4U

12VDC/1A Typical

PULSER POWER

12 VDC./500ma total

ENVIRONMENTAL

Temp: -40°C to 70°C

COMMUNICATION

Serial: RS 232/485

Ethernet TCP/IP, static IP

Wireless Point to Point

Wireless Ethernet

ENCLOSURE

Width: 25.3 cm / 10"

Height: 25.3 cm / 10"

Depth: 17cm / 6.75"

Weight: 2kg / 4.5 lbs

PEDESTAL

Stainless Steel

Width: 25.3 cm / 10"

40 cm / 16. (base)

Height: 150.5 cm / 59"

Depth: 6.35 cm / 2.5"

30 cm / 12. (base)

Weight: 13.5 kg / 30 lbs

ELECTRICAL REQUIREMENTS

ELECTRICAL REQUIREMENTS

Power Supply: 120 VAC, 1A

Pump Control, Each: 120 VAC, 15A max